



FREE STANDING WATER HEATERS						
CHARACTERISTICS						
Model	...	72280FWP	72281FZP	72282P	72289Z	72352(C)
Rated volume	L	150	200	300	500	1000
Rated pressure	MPa	0,8	0,8	0,8	0,8	0,6
Rated voltage	V~	230	230	380-400 3N (230)	380-400 3N (230)	380-400 3N
Rated electrical power	kW	3	3	9 (3)	9 (3)	9 (12 (C))
Warm-up time from 12-75 °C	h	3.7	4.9	2.2 (6.6)	4.15 (12.45)	8.3 (6.2)
MIX 37 °C (temperature of the water in the water tank: 75 °C; water temperature of supply water: 12 °C)	L	378	500	680	1260	2520
Weight when empty	kg	35	42	54	103	204
CONNECTIONS						
1: Thermometer-manometer		HE	HE	ДА	ДА	ДА
7: Flange with heating element		-	-	-	-	-
9: Cold water inlet - Drain		G3/4 F	G3/4 F	G3/4 F	G1 F	G1 1/2 F
10: Circulation		G3/4 F	G3/4 F	G3/4 F	G3/4 F	G3/4 F
11: Hot water outlet		G3/4 F	G3/4 F	G3/4 F	G1 F	G1 1/2 F
DIMENSIONS						
A	mm	230	230	230	280	365
C	mm	680	720	860	1015	1050
D	mm	620	670	670	810	1210
P	mm	885	925	1305	1440	1725
G	mm	85	85	85	85	100
H	mm	1170	1230	1610	1760	2150
M	mm	710	760	760	900	1150

"C" - electrical power 12kW